

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Edmond
2-5-02

2



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of: Amir SATRAN and Yaron EISEN

Application No.: To Be Assigned

Group Art Unit: To Be Assigned

Filed: Concurrently Herewith

Examiner: To Be Assigned

For: ROTARY CUTTING TOOL

Attorney Docket No.: 10236-039

CLAIM TO PRIORITY
TRANSMITTAL OF CERTIFIED COPY OF PRIORITY DOCUMENT

Assistant Commissioner for Patents
BOX PATENT APPLICATION
Washington, D.C. 20231

Sir:

Enclosed is a certified copy of Israeli Application Number 140104 filed December 5, 2000, in Israel, from which priority has been claimed in this application.

Respectfully submitted,

Date December 5, 2001

Nanda K. Alapati

Nanda K. Alapati Reg. No. 39,893
For: Marcia H. Sundeen Reg. No. 30,893

PENNIE & EDMONDS LLP
1667 K Street, N.W.
Washington, DC 20006
(202) 496-4400

Enclosure



מדינת ישראל
STATE OF ISRAEL

Ministry of Justice
Patent Office

משרד המשפטים
לשכת הפטנטים

11011 U.S. PTO
10/002180
12/05/01

This is to certify that annexed
hereto is a true copy of the
documents as originally
deposited with the patent
application of which
particulars are specified on the
first page of the annex.

זאת לתעודה כי רצופים
בזה העתקים נכונים של
המסמכים שהופקדו
לכתחילה עם הבקשה
לפטנט לפי הפרטים
הרשומים בעמוד הראשון
של הנספח.

19-11-2001
This היום

רשם הפטנטים
Commissioner of Patents

נתאשר
Certified

לשימוש הלשכה
For Office Use

חוק הפטנטים, תשכ"ז - 1967
PATENTS LAW, 5727-1967

ב ק ש ה ל פ ט נ ט
Application for Patent

מספר: Number	140104
תאריך: Date	05-12-00
הוקדם / נדחה Ante / Post-dated	

אני, (שם המבקש, מענו - ולגבי גוף מאוגד - מקום התאגדותו)
I, (Name and address of applicant, and, in case of a body corporate, place of incorporation)

ישקר בע"מ, חברה ישראלית, ת.ד. 11, תפן 24959, ישראל

Iscar Ltd., Israeli Company, P.O.Box 11, Tefen 24959, Israel

The inventors: Amir Satran
Yaron Eisen

הממציאים: אמיר סטרן
ירון איזן

ששמה הוא: Right of Law
Owner, by virtue of

בעל אמצאה מכח הדין
of an invention, the title of which is:

כלי שיבוב מסתובב

(בעברית)
(Hebrew)

Rotary Cutting Tool

(באנגלית)
(English)

hereby apply for a patent to be granted to me in respect thereof.

מבקש בזאת כי ינתן לי עליה פטנט.

* בקשת חלוקה Application for Division		* בקשת פטנט מוסף - Application for Patent of Addition		* דרישת דין קדימה Priority Claim	
מבקשת פטנט from Application		* לבקשה/לפטנט to Patent/Application		מספר/סימן Number/Mark	תאריך Date
No. _____ dated _____		מס' _____ dated _____			
* יפוי כח: כללי/מיוחד - רצוף/זה/עוד יוגש P.O.A.: general/specific - attached/to be filed later הוגש בענין 137316					
המען למסירת הודעות ומסמכים בישראל Address for Service in Israel					
Iscar Ltd. Patent Department P.O.Box 11 Tefen 24959		ישקר בע"מ מחלקת פטנטים ת.ד. 11 תפן 24959			
חתימת המבקש Signature of Applicant				היום 4 בחודש December שנת 2000	
M. Hays					
(Ref. No. 292-649130MK)					



לשימוש הלשכה
For Office Use

טופס זה, כשהוא מוטבע בחותם לשכת הפטנטים ומושלם במספר ובתאריך ההגשה, הינו אישור להגשת הבקשה שפרטיה רשומים לעיל.
This form, impressed with the Seal of the Patent Office and indicating the number and date of filing, certifies the filing of the application, the particulars of which are set out above.

• מחק את המיותר Delete whatever is inapplicable

כלי שיבוב מסתובב

Rotary Cutting Tool

Iscar Ltd.

ישקר בע"מ

The inventors:

הממציאים :

Amir Satran

אמיר סטרן

Yaron Eisen

ירון איזן

ROTARY CUTTING TOOL

FIELD AND BACKGROUND OF THE INVENTION

This invention relates to rotary cutting tools having a tool body the general form of a circular disk with cutting inserts secured tangentially to the circumference of the tool body, for metal machining in general and for machining
5 cam lobes of camshafts of internal combustion engines in particular. Such cutting tools normally employ groups of two or more cutting inserts arranged in a circumferentially staggered formation. The individual cutting edges of the cutting inserts in each group are generally oriented at non-zero lead angles. Consequently, each cutting insert has a non-zero axial component cutting force acting on it. Since
10 the cutting inserts are staggered, the cutting tool is unbalanced with respect to the axial component cutting forces.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a cutting tool of the
15 above general nature that replaces each group of cutting inserts arranged in a staggered formation by a single indexable cutting insert giving rise to a balanced cutting tool with respect to the axial component cutting forces.

In accordance with the present invention there is provided a rotary cutting tool comprising:

a tool body in the form of a circular disk having a center and a periphery, with an axis of rotation passing through the center of the disk and a plurality of chip clearance recesses opening outwardly from and spaced angularly around the disk periphery, each chip clearance recess having a leading end and a trailing end;

5 a plurality of insert receiving pockets, each insert receiving pocket having an associated chip clearance recess and comprising a tangentially extending pocket base having a leading end and a trailing end, the leading end of the pocket base being adjacent the trailing end of the associated chip clearance recess and the trailing end of the pocket base being connected to a generally radially
10 extending pocket rear surface;

a plurality of indexable cutting inserts, each cutting insert comprising an upper surface, a lower surface and a peripheral side surface therebetween, the peripheral side surface comprising four component side surfaces, each component side surface being joined to an adjacent side surface by a side corner,
15 an opposite pair of the component side surfaces forming front and rear component side surfaces, each component side surface meeting the upper and lower surfaces at upper and lower component cutting edges, respectively, at least outer portions of each upper and lower component cutting edge extending generally inwardly from adjacent side corners and at least outer portions of each
20 component side surface extending generally inwardly from adjacent side corners,

each cutting insert being removably retained in a given insert receiving pocket, wherein the lower surface of the cutting insert abuts the tangentially extending pocket base, the rear component side surface of the cutting insert abuts at two spaced apart abutment surfaces of the radially extending pocket rear surface,
25 the front component side surface forming a rake surface and the upper component cutting edge of the front component side surface forming an operative cutting edge with outer portions of the operative cutting edge forming equally leading portions thereof.

In order to secure the cutting inserts in position, the pocket base has a

radially extending threaded bore and each cutting insert of the plurality of cutting inserts has a through bore extending between the upper and lower surfaces and containing midpoints thereof, and each cutting insert is secured by a screw extending through the through bore and tightened into the threaded bore.

5 In accordance with a preferred embodiment of the present invention, each upper and lower component cutting edge is generally concave in form and each component side surface is generally concave in form extending inwardly from adjacent side corners.

10 Preferably, the upper and lower surfaces of the cutting insert each have a flat central portion for abutting the pocket base.

Further preferably, the upper and lower component cutting edges and the component side surfaces are divided into three portions, two outer portions and an inner portion, and the cutting insert is thicker in the region of the inner portion of the upper and lower component cutting edges than in the region of the
15 outer portion thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

20 **Fig. 1** is a perspective view of a rotary cutting tool in accordance with the present invention;

Fig. 2 is a perspective top view of a cutting insert receiving pocket in the rotary cutting tool shown in Fig. 1;

25 **Fig. 3** is a perspective view of a cutting insert retained in the rotary cutting tool in accordance with the present invention;

Fig. 4 is a top view of the cutting insert shown in Fig. 3;

Fig. 5 is a top view of a cutting insert receiving pocket in the rotary cutting tool shown in Fig. 1 with a cutting insert retained therein.

Fig. 6 is a cross section taken along the line VI-VI in Fig. 5; and

Fig. 7 is a front view of the cutting insert of the invention showing a component side surface having a chip-forming groove.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

5 Attention is drawn to the drawings in general and to Fig. 1 in particular, showing a rotary cutting tool in accordance with the present invention. The rotary cutting tool 10 comprises a tool body 12 in the form of a circular disk having a center 14 and a periphery 16. The rotary cutting tool 10 has an axis of rotation A that passes through the center 14 of the tool body 12. The tool body
10 12 has a plurality of chip clearance recesses 18 opening outwardly from and spaced angularly around the tool body 12 periphery 16, each chip clearance recess having a leading end 20 and a trailing end 22. It will be appreciated that the leading end 20 precedes the trailing end 22 with respect to the direction of rotation R of the rotary cutting tool 10.

15 Associated with each chip clearance recesses 18 is an insert receiving pocket 24. All the insert receiving pockets are at the same radial distance from the center 14 of the tool body 12. Each insert receiving pocket 24 comprises a tangentially extending pocket base 26 having a leading end 28 and a trailing end 30. The leading end 28 of the pocket base being adjacent the trailing end 22 of
20 the associated chip clearance recess 18. The trailing end 30 of the pocket base 26 being connected to a generally radially extending, substantially upright, pocket rear surface 32. It will be appreciated that the term radially extending, is defined with respect to the axis of rotation A, whereas the term upright, is defined relative to the pocket base 26. The pocket rear surface 32 and the pocket base 26 are
25 separated by a stress relief groove 34. It will be appreciated that when a workpiece (e.g., cam lobe) is machined, a leading portion of a given part of the cutting tool 10 will reach the workpiece before the trailing portion of that given part, as the cutting tool rotates.

As can be seen in the figures, each chip clearance recess 18 has a sloping

chip deflecting surface 36 that slopes upwardly from the trailing end 22 of the chip clearance recess 18 to the leading end 20 thereof where it joins a circumferential portion 38 at the periphery 16 of the tool body 12. As can be clearly seen in Figs. 2 and 6, the chip clearance recess 18 together the associated
5 insert receiving pocket 24 form a peripheral recess in the periphery 16 of the tool body 12. The circumferential portions 38 on either side of such a peripheral recess belong to the circumference of the tool body, which would be a complete cylindrical surface if it were not for the presence of the peripheral recesses.

In each insert receiving pocket 24 there is retained an indexable cutting
10 inserts 40. Each cutting insert 40 comprising an upper surface 42, a lower surface 44 and a peripheral side surface 46 therebetween. The upper surface 42 and lower surfaces 44 each have a flat central portion 48. The peripheral side surface 46 comprises four component side surfaces 50, 52, 54, 56, each component side surface being joined to an adjacent side surface by a side corner
15 58, 60, 62, 64. An opposite pair of component side surfaces form front 50 and rear 54 component side surfaces. In terms of the rotation of the rotary cutting tool 10, the front component side surface 50 is situated at the leading end of the cutting insert 40, whereas the rear component side surface 54 is situated at the trailing end of the cutting insert 40. Similarly, the side corners 58, 64 adjacent
20 the front component side surface 50 are leading side corners. Furthermore, each cutting insert 40 is oriented symmetrically with respect to the plane of rotation of the cutting tool 10 and therefore the leading side corners 58, 64 are equally leading side corners. Each component side surface 50, 52, 54, 56 meets the upper surface at upper component cutting edges 66', 68', 70', 72'. Likewise, each
25 component side surface 50, 52, 54, 56 meets the lower surface at lower component cutting edges 66'', 68'', 70'', 72''.

As seen in Fig. 3 and especially in the top view of the cutting insert 40 in Fig. 4, each upper component cutting edge 66', 68', 70', 72' and each lower component cutting edge 66'', 68'', 70'', 72'' is generally concave in form and

each component side surface 50, 52, 54, 56 is generally concave in form extending inwardly from adjacent side corners 58, 60, 62, 64. By generally concave is meant herein that the upper and lower component cutting edges and the component side surfaces could be, but do not have to be, strictly concave in the sense that portions thereof may be straight as long as they extend inwardly. With reference to Fig. 4, it will be noted that the operative cutting edge 66' (upper component cutting edge) is divided into three portions, two outer portions 66_o' and an inner portion 66_i'. The two outer portions 66_o' of the upper component cutting edge 66' are linear sections extending inwardly from adjacent side corners 58, 64 to the inner portion 66_i' and the inner portion 66_i' is a circular. In accordance with the definition given herein, the upper component cutting edge 66' is generally concave. In a similar manner all the upper component cutting edges and all the lower component cutting edge and the component side surfaces are generally concave and divided into three portions with the same geometry as the upper component cutting edge 66'.

The cutting insert 40 is removably retained in the insert receiving pocket 24 with the lower surface 44 of the cutting insert 40 abutting the tangentially extending pocket base 26 and two spaced apart abutment regions 74 of the rear component side surface 54 abutting the radially extending pocket rear surface 32 at two spaced apart abutment surfaces 76 that substantially match in shape the abutment regions 74 of the rear component side surface 54 of the cutting insert 40. It should be noted that the two spaced apart abutment regions 74 of the rear component side surface 54 are linear sections extending inwardly from adjacent side corners 60, 62, as described above with respect to the upper component cutting edge 66'.

With the cutting insert 40 retained in the insert receiving pocket 24, the front component side surface 50 forms a rake surface of the cutting insert 40 and the upper component cutting edge 66' of the front component side surface 50 forms an operative cutting edge of the cutting insert 40, with the outer portions 66_o'

forming leading portions of the operative cutting edge 66'. It should be noted that the two outer portions 66o' extend linearly inwardly with the same slope. It will be appreciated that cutting forces acting on the operative cutting edge 66' can be resolved into two mutually perpendicular component cutting forces, an axial and a tangential component. Since the two outer portions 66o' extend linearly inwardly with the same slope and since they lead by equal amounts, the axial component cutting forces acting on the two outer portions 66o' will be equal in magnitude but opposite in direction, and will therefore cancel each other out, giving rise to a balanced rotary cutting tool 10.

The pocket base 26 has a radially extending threaded bore 76 and the cutting insert 40 has a through bore 80 extending between the upper 42 and lower 44 surfaces. The through bore 80 is centrally located and therefore contains the midpoints of the upper 42 and lower 44 surfaces. The cutting insert 40 is removably retained in the insert receiving pocket 24 by a screw 82 which extends through the through bore 80 and is tightened into the threaded bore 76.

It will be appreciated that in order to machine a straight line on a section of a workpiece such as a cam lobe, the operative cutting edge has to lie on the cylindrical circumference of the tool body 12 and therefore the cutting insert 40 has to be thicker in the region of the inner portion 66i' than in the region of the outer portion 66o' of the operative cutting edge 66'. The same thickness relationship holds for all the component cutting edges. For a cutting insert having an average thickness of about 6 millimeters, a side length of about 20 millimeters with the central portion of the component side surface recessed by about 3 millimeters and for a tool body having a diameter of approximately 30 centimeters, the difference in thickness between the inner and outer portions of the cutting insert will be approximately 0.1 millimeter.

The cutting insert of the preferred embodiment is completely indexable in the sense that all four upper component cutting edges and all four lower component cutting edges can be used as operative cutting edges.

Although not an essential feature of the present invention, it will appreciated that the component side surfaces can include chip forming elements such as chip forming grooves and chip deflectors. As a non-limiting example, a component side surface of the cutting insert **40** of the invention can be provided
5 with a chip forming groove **84** as shown in a front view of the cutting insert in Fig. 7.

Although the present invention has been described to a certain degree of particularity, it should be understood that various alterations and modifications can be made without departing from the spirit or scope of the invention as hereinafter
10 claimed.

CLAIMS:

1. A rotary cutting tool comprising:

5 a tool body in the form of a circular disk having a center and a periphery, with an axis of rotation passing through the center of the disk and a plurality of chip clearance recesses opening outwardly from and spaced angularly around the disk periphery, each chip clearance recess having a leading end and a trailing end;

10 a plurality of insert receiving pockets, each insert receiving pocket having an associated chip clearance recess and comprising a tangentially extending pocket base having a leading end and a trailing end, the leading end of the pocket base being adjacent the trailing end of the associated chip clearance recess and the trailing end of the pocket base being connected to a generally radially extending pocket rear surface;

15 a plurality of indexable cutting inserts, each cutting insert comprising an upper surface, a lower surface and a peripheral side surface therebetween, the peripheral side surface comprising four component side surfaces, each component side surface being joined to an adjacent side surface by a side corner, an opposite pair of the component side surfaces forming front and rear component side surfaces, each component side surface meeting the upper and lower surfaces at upper and lower component cutting edges, respectively, at least 20 outer portions of each upper and lower component cutting edge extending generally inwardly from adjacent side corners and at least outer portions of each component side surface extending generally inwardly from adjacent side corners,

25 each cutting insert being removably retained in a given insert receiving pocket, wherein the lower surface of the cutting insert abuts the tangentially extending pocket base, the rear component side surface of the cutting insert abuts the radially extending pocket rear surface at two spaced apart abutment surfaces, the front component side surface forming a rake surface and the upper component cutting edge of the front component side surface forming an operative cutting edge.

2. The rotary cutting tool according to Claim 1, wherein the pocket base has a radially extending threaded bore and each cutting insert of the plurality of cutting inserts has a through bore extending between the upper and lower surfaces and containing midpoints thereof, and each cutting insert is removably retained
5 by a screw extending through the through bore and tightened into the threaded bore.
3. The rotary cutting tool according to Claim 1, wherein each upper and lower component cutting edge is generally concave in form and each component side surface is generally concave in form extending inwardly from adjacent side
10 corners.
4. The rotary cutting tool according to Claim 1, wherein the upper and lower surfaces of the cutting insert each have a flat central portion.
5. The rotary cutting tool according to Claim 1, wherein the upper and lower component cutting edges and the component side surfaces are divided into
15 three portions, two outer portions and an inner portion, the two outer portions being linear sections and the inner portion being a circular and wherein the cutting insert is thicker in the region of the inner portion than in the region of the outer portion.
6. The rotary cutting tool according to Claim 1, wherein the upper and
20 lower component cutting edges and the component side surfaces are divided into three portions, two outer portions and an inner portion, and the cutting insert is thicker in the region of the inner portion of the upper and lower component cutting edges than in the region of the outer portion thereof.

M. Kay




Fig. 1







Fig. 2






Fig. 5




Fig. 6